



Enable Item Barcode Conversion

Megan De Freitas - 2025-06-11 - System

Overview

Scan any UPC/barcode into SalesPad and it will convert the barcode number to the stored customer item number on the sales document.

Setup

When the *Enable Item Barcode Conversion* setting is set to True, SalesPad will use a stored procedure to convert item numbers.

- With the default stored procedure (spvItemBarcode) in place, a vendor number added to a sales document will automatically be replaced by the actual (inventory) item number (See also: [Vendor Items](#) document).
- With a modified custom stored procedure (replace spvItemBarcode with spcplItemBarcode), any UPC barcode stored on a SalesPad user field can be scanned onto a sales document and converted to the Dynamics GP item number.

The following stored procedure, spcplItemBarcode, can be used to customize the way the item barcode conversion works. The example below assumes that the UPC/Barcode value is stored in a SalesPad Item user field called xUPC:

```
/****** Object: StoredProcedure [dbo].[spcplItemBarcode] *****/
```

```
SET ANSI_NULLS ON
```

```
GO
```

```
SET QUOTED_IDENTIFIER ON GO
```

```
CREATE PROCEDURE [dbo].[spcplItemBarcode] @Barcode AS VARCHAR(100) = NULL
```

```
,@Customer_Number AS VARCHAR(100) = NULL
```

```
AS
```

```
BEGIN
```

```
SELECT TOP 1 Item_Number
```

```
,Barcode
```

```
FROM (
```

```
SELECT Item_Number = ISNULL(ivm.ITEMNMBR, "")
```

```
,Barcode = ISNULL(ivm.VNDITNUM, "")
```

```
FROM IV00103 AS ivm(NOLOCK) --item vendor master
```

```
UNION
```

```
SELECT Item_Number = ISNULL(ci.ITEMNMBR, "")
,Barcode = ISNULL(ci.CUSTITEMNMBR, "")
FROM SOP60300 AS ci(NOLOCK) --customer items
```

UNION

```
SELECT Item_Number = ISNULL(im.Item_Number, "")
,Barcode = ISNULL(im.xUPC, "")
FROM spvItemMaster AS im --item UPC codes
) AS a
WHERE Barcode = @Barcode
END
```

Example

1. In the User Field Editor, create a user field on the Item Master (refer to the SalesPad [User Defined Fields](#) document) for storing UPC/barcodes (whatever you call the user field, the spcp must be edited to use this name. For example, in the procedure above, the user field is named xUPC)
2. In Inventory Lookup, select an item and enter or scan the UPC or other barcode id into the user field (repeat for each item as needed)
3. Open a sales document (or use [Counter Sales](#)) and scan a barcode onto a new line item

Security

Enable Item Barcode Conversion - Allows the use of a procedure to translate a barcode value to an item number in SalesPad